L70+/L70F-HNL7 L70+/L70F/P5 DIP SWITCHES SETTING: 1(Pulse/ICT104U)

Supported bill HNL 5, 10, 20, 50, 100, 200, 500 7bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
*	1 Pulse / HNL 5	OFF	OFF	OFF							
	2 Pulses / HNL 5	OFF	OFF	ON							
	3 Pulses / HNL 5	OFF	ON	OFF							
	4 Pulses / HNL 5	OFF	ON	ON							
	5 Pulses / HNL 5	ON	OFF	OFF							
	10 Pulses / HNL 5	ON	OFF	ON							
	20 Pulses / HNL 5	ON	ON	OFF							
	100 Pulses / HNL 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
*	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
*	Inhibit level Active High					OFF					
*	Accept HNL 5 & 10						ON				
	Reject HNL 5 & 10						OFF				
*	Accept HNL 20							ON			
	Reject HNL 20							OFF			
*	Accept HNL 50								ON		
	Reject HNL 50								OFF		
*	Accept HNL 100 & 200									ON	
	Reject HNL 100 & 200									OFF	
*	Accept HNL 500										ON
	Reject HNL 500										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

Appendix

L70+/L70F-HNL7(Pulse/ICT104U)

DIP SWITCHES SETTING: 2(Pulse) Currency Assign Data

	FUNCTION	SW1	SW2	SW3	SW4
k	Credit - Pulse Normal High	ON			
	Credit - Pulse Normal Low	OFF			
k	Pulse Mode		ON		
	ICT104U Mode		OFF		
k				ON	
	Reserved			OFF	
	Reserved				ON
k				OFF	

Interface Bill value	Pulse	ICT104U		
BV1	HNL 5	HNL 5		
BV2	HNL 10	HNL 10		
BV3	HNL 20	HNL 20		
BV4	HNL 50	HNL 50		
BV5	HNL 100	HNL 100		
BV6	HNL 200	HNL 200		
BV7	HNL 500	HNL 500		

DIP SWITCHES SETTING: 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
*	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
*	ICT104U Mode		OFF		
*	Reserved			ON	
				OFF	
	Reserved		ON		
*					OFF