RUR5

L70/P5 DIP SWITCHES SETTING: 1(Special Pulse/ICT)

Supported bill p. 10, 50, 100, 500, 1000 5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
*	1 Pulse / p. 10 (Note.3)	OFF	OFF	OFF							
	2 Pulse / p. 10	OFF	OFF	ON							
	3 Pulse / p. 10	OFF	ON	OFF							
	4 Pulse / p. 10	OFF	ON	ON							
	5 Pulse / p. 10	ON	OFF	OFF							
	10 Pulse / p. 10	ON	OFF	ON							
	20 Pulse / p. 10	ON	ON	OFF							
	100 Pulse / p. 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
*	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
*	Inhibit level Active High					OFF					
*	Accept p. 10 (Note.3)						ON				
	Reject p. 10 (Note.3)						OFF				
*	Accept p. 50							ON			
	Reject p. 50							OFF			
*	Accept p. 100								ON		
	Reject p. 100								OFF		
*	Accept p. 500									ON	
	Reject p. 500									OFF	
*	Accept p. 1000										ON
	Reject p. 1000										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

- (2) Dip switches 1 to 5 are only used for pulse protocol.
- (3) **Pulse**: When Dip 6 is ON (Accept p. 10), One Pulse per p. 10. When Dip 6 is OFF (Reject p. 10), One Pulse per p. 50.

ICT: When Dip 6 is ON(Accept p. 10), BV1=40 BV2=41 BV3=42 BV4=43 BV5=44.
When Dip 6 is OFF(Reject p. 10) BV2=40 BV3=41 BV4=42 BV5=43.

L70-RUR5/P5(Special Pulse/ICT)

DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
*	Pulse Mode		ON		
	ICT Interface		OFF		
*	Description				
	Reserved		ON		
*					OFF

[★] Manufacture setting

DIP SWITCHES SETTING: 2(ICT)

	FUNCTION	SW1	SW2	SW3	SW4
*	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
*	ICT Interface		OFF		
	Reserved			ON	
*				OFF	
*			OFF		

[★] Manufacture setting

Currency Assign Data

Interface Bill value	ICT	Pulse
BV1	10	10
BV2	50	50
BV3	100	100
BV4	500	500
BV5	1000	1000