



### VND3

## L70/P5 DIP SWITCHES SETTING : 1(Pulse/M.D.B)

Supported bill VND 10000, 20000, 50000 3bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / VND 10000	OFF	OFF	OFF							
	2 Pulse / VND 10000	OFF	OFF	ON							
	3 Pulse / VND 10000	OFF	ON	OFF							
	4 Pulse / VND 10000	OFF	ON	ON							
	5 Pulse / VND 10000	ON	OFF	OFF							
	10 Pulse / VND 10000	ON	OFF	ON							
	20 Pulse / VND 10000	ON	ON	OFF							
	100 Pulse / VND 10000	ON	ON	ON							
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept VND 10000				ON						
★	Reject VND 10000				OFF						
★	Accept VND 20000				ON						
	Reject VND 20000				OFF						
★	Accept VND 50000				ON						
	Reject VND 50000				OFF						
★	Reserved				ON						
					OFF						
					ON						
★					OFF						

★ Manufacture setting

- Note: (1) Please reset the bill acceptor after set the dip switch.  
 (2) Dip switches 1 to 5 are only used for pulse protocol.

# **L70-VND3/P5(Pulse/M.D.B)**

## **DIP SWITCHES SETTING : 2(Pulse)**

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	M.D.B Interface		OFF		
★	Reserved			ON	
				OFF	
★					ON
					OFF

★ Manufacture setting

## **DIP SWITCHES SETTING : 3(M.D.B)**

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON		
★	M.D.B Interface		OFF		
★	Reserved			ON	
				OFF	
★					ON
					OFF

★ Manufacture setting