

L70+/L70F-NIO7

L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0/Parallel A1)

Supported bill C\$ 10, 20, 50, 100, 200, 500, 1000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★ 1 Pulse / C\$ 10	OFF	OFF	OFF								
2 Pulses / C\$ 10	OFF	OFF	ON								
3 Pulses / C\$ 10	OFF	ON	OFF								
4 Pulses / C\$ 10	OFF	ON	ON								
5 Pulses / C\$ 10	ON	OFF	OFF								
10 Pulses / C\$ 10	ON	OFF	ON								
20 Pulses / C\$ 10	ON	ON	OFF								
100 Pulses / C\$ 10	ON	ON	ON								
Fast output Pulse (Lo=50ms/ Hi=100ms) / IGT(Lo=20ms/ Hi=20ms)											ON
★ Slow output (Lo=50ms/ Hi=300ms) / IGT(Lo=20ms/ Hi=20ms)											OFF
Inhibit level Active Low					ON						
★ Inhibit level Active High					OFF						
★ Accept C\$ 10 & 20						ON					
Reject C\$ 10 & 20						OFF					
★ Accept C\$ 50 & 100							ON				
Reject C\$ 50 & 100							OFF				
★ Accept C\$ 200								ON			
Reject C\$ 200								OFF			
★ Accept C\$ 500									ON		
Reject C\$ 500									OFF		
★ Accept C\$ 1000										ON	
Reject C\$ 1000										OFF	

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70+/L70F-NIO7/P5(Pulse/RS232 A0/Parallel A1)

DIP SWITCHES SETTING : 2(Pulse) Currency Assign Data

FUNCTION	SW1	SW2	SW3	SW4	
★ Pulse Normal High	ON				
Pulse Normal Low	OFF				
★ Pulse Mode		ON	OFF		
RS232 A0 Mode		OFF	OFF		
Parallel A1 Mode		OFF	ON		
Reserved		ON	ON		
Reserved					ON
					OFF

★ Manufacture setting

Interface Bill value	Parallel A1	Pulse	RS232 A0
BV1	C\$ 10	C\$ 10	C\$ 10
BV2	C\$ 20	C\$ 20	C\$ 20
BV3	C\$ 50	C\$ 50	C\$ 50
BV4	C\$ 100	C\$ 100	C\$ 100
BV5	C\$ 200	C\$ 200	C\$ 200
BV6	C\$ 500	C\$ 500	C\$ 500
BV7	C\$ 1000	C\$ 1000	C\$ 1000

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4	
★ Reserved	ON				
	OFF				
Pulse Mode		ON	OFF		
★ RS232 A0 Mode		OFF	OFF		
Parallel A1 Mode		OFF	ON		
Reserved		ON	ON		
Reserved					ON
					OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	C\$ 10
2	Reserved
3	C\$ 50
4	C\$ 100
5	C\$ 200
6	C\$ 500
7	C\$ 1000
8	Reserved
9	Reserved

★ Manufacture setting

Note: Rs232 A0 interface Accept NIO\$20 transform send twice USD\$1 credit.

DIP SWITCHES SETTING : 2(Parallel A1)

FUNCTION	SW1	SW2	SW3	SW4	
★ Reserved	ON				
	OFF				
Pulse Mode		ON	OFF		
RS232 A0 Mode		OFF	OFF		
★ Parallel A1 Mode		OFF	ON		
Reserved		ON	ON		
Reserved					ON
					OFF

★ Manufacture setting