

P77-CZK6

P77/P5 DIP SWITCHES SETTING : 1(Pulse/GBA Rs232)

Supported bill Kč 100, 200, 500, 1000, 2000, 5000 6bills.

With stacker Kč 100, 200, 500, 1000, 2000, 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Kč 50	OFF	OFF	OFF							
2 Pulse / Kč 50	OFF	OFF	ON							
3 Pulse / Kč 50	OFF	ON	OFF							
4 Pulse / Kč 50	OFF	ON	ON							
5 Pulse / Kč 50	ON	OFF	OFF							
10 Pulse / Kč 50	ON	OFF	ON							
20 Pulse / Kč 50	ON	ON	OFF							
100 Pulse / Kč 50	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi = 100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi = 300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept Kč 100						ON				
Reject Kč 100						OFF				
★ Accept Kč 200 & 500							ON			
Reject Kč 200 & 500							OFF			
★ Accept Kč 1000								ON		
Reject Kč 1000								OFF		
★ Accept Kč 2000									ON	
Reject Kč 2000									OFF	
★ Accept Kč 5000										ON
Reject Kč 5000										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2 Currency Assign Data

FUNCTION		SW1	SW2	SW3	SW4	Interface	GBA Rs232	Pulse
GBA RS232 Protocol	Pulse Protocol					Bill value		
★ Reserved	Credit-Pulse Normal High	ON				BV1		
Reserved	Credit-Pulse Normal Low	OFF				BV2	Kč 100	Kč 100
Pulse Protocol	★ Pulse Protocol		ON			BV3	Kč 200	Kč 200
★ GBA Rs232 Protocol	GBA Rs232 Protocol		OFF			BV4	Kč 500	Kč 500
Reserved	Harness Disable			ON		BV5	Kč 1000	Kč 1000
★ Reserved	Harness Enable			OFF		BV6	Kč 2000	Kč 2000
Reserved					ON	BV7	Kč 5000	Kč 5000
★ Reserved					OFF			

★ Manufacture setting

Note : (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 & 3 are only used for pulse protocol.