

P77-KGS7

P77/P5 DIP SWITCHES SETTING : 1(Pulse/M.D.B/ICT104U)

Supported bill KGS 20, 50, 100, 200, 500, 1000, 5000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / KGS 10 & 50 (Note.3)	OFF	OFF	OFF							
2 Pulse / KGS 10 & 50 (Note.3)	OFF	OFF	ON							
3 Pulse / KGS 10 & 50 (Note.3)	OFF	ON	OFF							
4 Pulse / KGS 10 & 50 (Note.3)	OFF	ON	ON							
5 Pulse / KGS 10 & 50 (Note.3)	ON	OFF	OFF							
10 Pulse / KGS 10 & 50 (Note.3)	ON	OFF	ON							
20 Pulse / KGS 10 & 50 (Note.3)	ON	ON	OFF							
100 Pulse / KGS 10 & 50 (Note.3)	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept KGS 20						ON				
Reject KGS 20						OFF				
★ Accept KGS 50 & 100						ON				
Reject KGS 50 & 100						OFF				
★ Accept KGS 200 & 500							ON			
Reject KGS 200 & 500							OFF			
★ Accept KGS 1000								ON		
Reject KGS 1000								OFF		
★ Accept KGS 5000									ON	
Reject KGS 5000									OFF	

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

(3) Pulse Mode:

When Dip 6 is ON ,One Pulse per KGS 10.

When Dip 6 is OFF,One Pulse per KGS 50.

(4) MDB Mode:

When Dip 6 is ON ,Reject KGS 5000.

When Dip 6 is OFF,Accept KGS 5000.

P77-KGS7/P5(Pulse/M.D.B/ICT104U)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
Other Interface		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(M.D.B)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
Other Interface		OFF		
★ Reserved			ON	
			OFF	
ICT104U Protocol				ON
★ MDB Protocol (SW2 OFF)				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON		
Other Interface		OFF		
★ Reserved			ON	
			OFF	
★ ICT104U Protocol (SW2 OFF)				ON
MDB Protocol				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse		ICT104U	MDB	
	Dip 6 ON	Dip 6 OFF		Dip 6 ON	Dip 6 OFF
BV1	KGS 20		KGS 20	KGS 20	KGS 50
BV2	KGS 50	KGS 50	KGS 50	KGS 50	KGS 100
BV3	KGS 100	KGS 100	KGS 100	KGS 100	KGS 200
BV4	KGS 200	KGS 200	KGS 200	KGS 200	KGS 500
BV5	KGS 500	KGS 500	KGS 500	KGS 500	KGS 1000
BV6	KGS 1000	KGS 1000	KGS 1000	KGS 1000	KGS 5000
BV7	KGS 5000	KGS 5000	KGS 5000		