



KGS8

P77/P5 DIP SWITCHES SETTING : 1 (Pulse/MDB)

**Supported bill SOM 5, 10, 20, 50, 100, 200, 500, 1000
8bills.**

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / SOM 5	OFF	OFF	OFF							
	2 Pulse / SOM 5	OFF	OFF	ON							
	3 Pulse / SOM 5	OFF	ON	OFF							
	4 Pulse / SOM 5	OFF	ON	ON							
	5 Pulse / SOM 5	ON	OFF	OFF							
	10 Pulse / SOM 5	ON	OFF	ON							
	20 Pulse / SOM 5	ON	ON	OFF							
	100 Pulse / SOM 5	ON	ON	ON							
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept SOM 5 & 10				ON						
	Reject SOM 5 & 10				OFF						
★	Accept SOM 20 & 50				ON						
	Reject SOM 20 & 50				OFF						
★	Accept SOM 100 & 200				ON						
	Reject SOM 100 & 200				OFF						
★	Accept SOM 500				ON						
	Reject SOM 500				OFF						
★	Accept SOM 1000				ON						
	Reject SOM 1000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON		
★	MDB Interface		OFF		
	Reserved			ON	
★					OFF
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting