

RSD7

P77/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill ДИН 10, 20, 50, 100, 200, 500, 1000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / ДИН 10	OFF	OFF	OFF							
2 Pulse / ДИН 10	OFF	OFF	ON							
3 Pulse / ДИН 10	OFF	ON	OFF							
4 Pulse / ДИН 10	OFF	ON	ON							
5 Pulse / ДИН 10	ON	OFF	OFF							
10 Pulse / ДИН 10	ON	OFF	ON							
20 Pulse / ДИН 10	ON	ON	OFF							
100 Pulse / ДИН 10	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept ДИН 10 & 20						ON				
Reject ДИН 10 & 20						OFF				
★ Accept ДИН 50 & 100							ON			
Reject ДИН 50 & 100							OFF			
★ Accept ДИН 200								ON		
Reject ДИН 200								OFF		
★ Accept ДИН 500									ON	
Reject ДИН 500									OFF	
★ Accept ДИН 1000										ON
Reject ДИН 1000										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
★ Harness Disable			ON	
Harness Enable			OFF	
★ Manufacture Default				ON
System Default				OFF

★ Manufacture setting.