P85-TRY6

P85/P5 DIP SWITCHES SETTING: 1(Pulse/ICT)

Supported bill TRY 5, 10, 20, 50, 100, 200

6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
⋆┃	1 Pulse / TRY 5	OFF	OFF	OFF							
	2 Pulse / TRY 5	OFF	OFF	ON							
	3 Pulse / TRY 5	OFF	ON	OFF							
	4 Pulse / TRY 5	OFF	ON	ON							
	5 Pulse / TRY 5	ON	OFF	OFF							
	10 Pulse / TRY 5	ON	OFF	ON							
	20 Pulse / TRY 5	ON	ON	OFF							
	100 Pulse / TRY 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
*	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
\star	Inhibit level Active High					OFF					
\star	Accept TRY 5 & 10						ON				
	Reject TRY 5 & 10						OFF				
\star	Accept TRY 20							ON			
	Reject TRY 20							OFF			
*	Accept TRY 50								ON		
	Reject TRY 50								OFF		
*	Accept TRY 100									ON	
	Reject TRY 100									OFF	
\star	Accept TRY 200										ON
	Reject TRY 200										OFF

[★] Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

DIP SWITCHES SETTING: 2

_					
	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	Pulse Normal High ON			
	Pulse Normal Low	OFF			
*	Pulse Protocol		ON		
	ICT Protocol		OFF		
	Harness Disable			ON	
*	Harness Enable			OFF	
	Manufacture Default				ON
*	System Default				OFF

Currency Assign Data

Interface Bill value	ICT104	Pulse
BV1	5	5
BV2	10	10
BV3	20	20
BV4	50	50
BV5	100	100
BV6	200	200

Appendix

© 2007 International Currency Technologies Corporation V. 2.0 Part Number : SWB0TR620-R

⁽²⁾ Dip switches 1 to 5 are only used for pulse protocol.

[★] Manufacture setting