

TAO-V-BRL5

TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill R\$ 2, 5, 10, 20, 50 5bills.

TAO-V dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject R\$ 2	ON											
★ Accept R\$ 2	OFF											
★ Reject R\$ 5		ON										
★ Accept R\$ 5		OFF										
★ Reject R\$ 10			ON									
★ Accept R\$ 10			OFF									
★ Reject R\$ 20				ON								
★ Accept R\$ 20				OFF								
★ Reject R\$ 50					ON							
★ Accept R\$ 50					OFF							
★ Reserved						ON						
★ Reserved						OFF						
Pulse Mode	Other Mode											
★ Harness Disable	BA stops working when fishing						ON					
★ Harness Enable	Normal						OFF					
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / R\$ 1									OFF	OFF		
★ 2 pulses / R\$ 1									ON	OFF		
★ 4 pulses / R\$ 1									OFF	ON		
★ 10 pulses / R\$ 1									ON	ON		
★ Interface Timing Conversion	50ms LO / 50ms HI										OFF	OFF
	60ms LO / 300ms HI										ON	OFF
	30ms LO / 50ms HI										OFF	ON
	150ms LO / 150ms HI										ON	ON

★ Manufacture setting

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

TAO-V-BRL5(Pulse/MDB)

Interface Settings: 3(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
MDB Protocol		OFF		
★ Reserved			ON	
			OFF	
				ON
★ Reserved				OFF

★ Manufacture setting

Interface Settings: 3(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	OFF			
★ Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
★ Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
★ Reserved				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	R\$ 2	R\$ 2
BV2	R\$ 5	R\$ 5
BV3	R\$ 10	R\$ 10
BV4	R\$ 20	R\$ 20
BV5	R\$ 50	R\$ 50