## **UCA Series**

# Coin Acceptor

- Low power consumption
- Eight coin channels available at once.
- Mechanical and electrical anti-string functions.



## **Coin Acceptor**

UCA series is designed as reliable coin acceptors which are able to work steadily in high temperature for high-security with acceptance rate up to 96% or greater. Moreover, UCA Series includes UCA2 and UCAES for different accepted coins and applications to fulfill your needs.

#### **Specifications**



#### Acceptance Rate

96% or greater



#### **Power Consumption**

Standby: 0.05A, 0.6W Operation: 0.2A, 2.4W Maximum: 0.5A, 6W



#### Acceptance Speed

Approx. 3 coins/sec.



#### Dimension

147.5 x 72.4 x 124 mm/ 14.55 x 5.81 x 4.88inches



#### Interface

RS232 (TTL level)



#### Weight

Approx. 0.35 kg/0.77 lbs



#### Coin Parameters

Diameter: 20~32 mm/0.78~1.25 inches Thickness: 1.2~3.2 mm/0.05~0.13 inches



#### Environmental

Operating Temperature: -5°C~60°C Storage Temperature : -20°C~75°C Humidity: 30%~85%RH(no condensation)



#### Power Source

12V±10% (10.8V~13.2V DC)



#### Recommended Applications

Indoor/Vending, Kiosk, Amusement

-Specifications are subject to change without prior notice.









### **International Currency Technologies**

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan Phone: +886-2-2793-1236
Fax: +886-2-2793-6125
EMail: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Product Information fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw