

A6/V6-AED5

A6/V6 Option Switch Settings: 1

Supported bill Dh 5, 10, 20, 50, 100

5bills.

A6/V6 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject Dh 5	ON											
	Accept Dh 5	OFF											
	Reject Dh 10		ON										
★	Accept Dh 10		OFF										
	Reject Dh 20			ON									
★	Accept Dh 20			OFF									
	Reject Dh 50				ON								
★	Accept Dh 50				OFF								
	Reject Dh 100					ON							
★	Accept Dh 100					OFF							
	Reserved						ON						
★	Reserved						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / Dh 5									OFF	OFF		
	2 pulses / Dh 5									ON	OFF		
	4 pulses / Dh 5									OFF	ON		
	20 pulses / Dh 5									ON	ON		
★	Interface Timing Conversion	50ms on / 50ms off								OFF	OFF		
		60ms on / 300ms off								ON	OFF		
		30ms on / 50ms off								OFF	ON		
		150ms on / 150ms off								ON	ON		

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A6/V6-AED5

A6 Interface Settings: 2(Pulse/RS232)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	RS232 Interface		OFF		
	Reserved			ON	
★				OFF	
					ON
★					OFF

★ Manufacture setting

	INTERFACE	SW1	SW2	SW3	SW4
	Reserved	ON			
★		OFF			
	Pulse Mode		ON		
★	RS232 Interface		OFF		
	Reserved			ON	
★				OFF	
					ON
★					OFF

★ Manufacture setting

V6 Interface Settings: 2(M.D.B)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100	ON			
	Decimal Point Position (DPP) = 2				
	Scaling Factor (SF) = 1	OFF			
	Decimal Point Position (DPP) = 0				
	Reserved		ON		
★	M.D.B Interface		OFF		
	Reserved			ON	
★				OFF	
					ON
★					OFF

★ Manufacture setting