

V6-AUD5

V6 Option Switch Settings: (AC 24V Pulse)

Supported bill \$A 5, 10, 20, 50, 100 5bills.

V6 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject \$A 5	ON											
Accept \$A 5	OFF											
Reject \$A 10		ON										
Accept \$A 10		OFF										
Reject \$A 20			ON									
Accept \$A 20			OFF									
Reject \$A 50				ON								
Accept \$A 50				OFF								
Reject \$A 100					ON							
Accept \$A 100					OFF							
Reserved						ON						
Reserved						OFF						
Harness Disable							ON					
Harness Enable							OFF					
★ Inhibit Active High								ON				
Reserved								OFF				
1 pulse / \$A 5									OFF	OFF		
★ 5 pulse / \$A 5									ON	OFF		
10 pulse / \$A 5									OFF	ON		
20 pulse / \$A 5									ON	ON		
Interface Timing Conversion	50ms on / 50ms off										OFF	OFF
	60ms on / 300ms off										ON	OFF
	30ms on / 50ms off										OFF	ON
	150ms on / 150ms off										ON	ON

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.