

**A7/V7 Option Switch Settings**

Supported bill somoni 1, 5, 10 3bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject somoni 1	ON											
★ Accept somoni 1	OFF											
★ Reject somoni 5		ON										
★ Accept somoni 5		OFF										
★ Reject somoni 10			ON									
★ Accept somoni 10			OFF									
★ Reserved				ON								
★ Reserved				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness disable							ON					
★ Harness enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / somoni 1									OFF	OFF		
★ 2 pulse / somoni 1									ON	OFF		
★ 5 pulse / somoni 1									OFF	ON		
★ 20 pulse / somoni 1									ON	ON		
★ Pulse Speed	50ms on / 50ms off								OFF	OFF		
	60ms on / 300ms off								ON	OFF		
	30ms on / 50ms off								OFF	ON		
	150ms on / 150ms off								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

**A7 Interface Settings: 2**

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

**V7 Interface Settings: 3**

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	ON			
	OFF			
★ Scaling Factor (SF) = 10 Decimal Point Position (DPP) = 1				
Pulse Mode		ON		
★ MDB interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

