

V7-HUF6

V7 Option Switch Settings : 1(Pulse/Parallel A3/MDB)

Supported bill Ft 500, 1000, 2000, 5000, 10000, 20000 6bills.

V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Ft 500	ON											
★ Accept Ft 500	OFF											
Reject Ft 1000		ON										
★ Accept Ft 1000		OFF										
Reject Ft 2000			ON									
★ Accept Ft 2000			OFF									
Reject Ft 5000&10000				ON								
★ Accept Ft 5000&10000				OFF								
Reject Ft 20000					ON							
★ Accept Ft 20000					OFF							
Reserved						ON						
★ Reserved						OFF						
Harness Disable							ON					
★ Harness Enable							OFF					
Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / Ft 500									OFF	OFF		
5 pulses / Ft 500									ON	OFF		
10 pulses / Ft 500									OFF	ON		
20 pulses / Ft 500									ON	ON		
★ Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
	60ms LO / 300ms HI								ON	OFF		
	30ms LO / 50ms HI								OFF	ON		
	150ms LO / 150ms HI								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Sw7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

(3) Parallel A3 Mode only Accept 500,1000,2000,5000 (4 bills)

V7-HUF6(Pulse/Parallel A3/MDB)

Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Interface		ON	OFF	
Parallel A3 Interface		OFF	ON	
MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Settings: 2(Parallel A3) Currency Assign Data

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Interface		ON	OFF	
★ Parallel A3 Interface		OFF	ON	
MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Bill value	Parallel A3	Pulse	MDB
BV1	HUF 500	HUF 500	HUF 500
BV2	HUF 1000	HUF 1000	HUF 1000
BV3	HUF 2000	HUF 2000	HUF 2000
BV4	HUF 5000	HUF 5000	HUF 5000
BV5		HUF 10000	HUF 10000
BV6		HUF 20000	HUF 20000

Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 2 Decimal Point Position (DPP) = 100	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Interface		ON	OFF	
Parallel A3 Interface		OFF	ON	
★ MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting