

### V7-ROL3

### V7 Option Switch Settings : 1(Pulse/Parallel A3/MDB)

Supported bill Lei 1, 5, 10 3bills.

V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Lei 1	ON											
★ Accept Lei 1	OFF											
★ Reject Lei 5		ON										
★ Accept Lei 5		OFF										
★ Reject Lei 10			ON									
★ Accept Lei 10			OFF									
★ Reserved				ON								
★ Reserved				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness Disable							ON					
★ Harness Enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / Lei 1									OFF	OFF		
★ 2 pulses / Lei 1									ON	OFF		
★ 5 pulses / Lei 1									OFF	ON		
★ 20 pulses / Lei 1									ON	ON		
★ Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
	60ms LO / 300ms HI								ON	OFF		
	30ms LO / 50ms HI								OFF	ON		
	150ms LO / 150ms HI								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the acceptor after setting the dip switch.

(2) Sw7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

### V7-ROL3(Pulse/Parallel A3/MDB)

#### Interface Settings: 3(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Interface		ON	OFF	
Parallel A3 Interface		OFF	ON	
MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

#### Interface Settings: 3(Parallel A3)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Interface		ON	OFF	
★ Parallel A3 Interface		OFF	ON	
MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

#### Currency Assign Data

Interface Bill value	MDB	Pulse	Parallel A3
BV1	Lei 1	Lei 1	Lei 1
BV2	Lei 5	Lei 5	Lei 5
BV3	Lei 10	Lei 10	Lei 10

#### Interface Settings: 3(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 2 Decimal Point Position (DPP) = 100	ON			
	OFF			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0				
Pulse Interface		ON	OFF	
Parallel A3 Interface		OFF	ON	
★ MDB Interface		OFF	OFF	
Reserved		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting