

L70+/L70F-SYP6

L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U/MDB)

Supported bill SYP 10, 25, 50, 100, 200, 500 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / SYP 5	OFF	OFF	OFF							
	2 Pulse / SYP 5	OFF	OFF	ON							
	3 Pulse / SYP 5	OFF	ON	OFF							
	4 Pulse / SYP 5	OFF	ON	ON							
	5 Pulse / SYP 5	ON	OFF	OFF							
	10 Pulse / SYP 5	ON	OFF	ON							
	20 Pulse / SYP 5	ON	ON	OFF							
	100 Pulse / SYP 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept SYP 10 & SYP 25						ON				
	Reject SYP 10 & SYP 25						OFF				
★	Accept SYP 50							ON			
	Reject SYP 50							OFF			
★	Accept SYP 100								ON		
	Reject SYP 100								OFF		
★	Accept SYP 200									ON	
	Reject SYP 200									OFF	
★	Accept SYP 500										ON
	Reject SYP 500										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70+/L70F-SYP6(Pulse/ICT104U/MDB)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Interface		OFF	ON	
	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT104U	Pulse	MDB
BV1	SYP 10	SYP 10	SYP 10
BV2	SYP 25	SYP 25	SYP 25
BV3	SYP 50	SYP 50	SYP 50
BV4	SYP 100	SYP 100	SYP 100
BV5	SYP 200	SYP 200	SYP 200
BV6	SYP 500	SYP 500	SYP 500

DIP SWITCHES SETTING : 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Interface		OFF	ON	
	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT104U Interface		OFF	ON	
★	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting