

L70-NAD7

L70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U)

Supported bill NAD 10, 20, 30, 50, 60, 100, 200 7 bills.

★	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / NAD 10	OFF	OFF	OFF							
	2 Pulses / NAD 10	OFF	OFF	ON							
	3 Pulses / NAD 10	OFF	ON	OFF							
	4 Pulses / NAD 10	OFF	ON	ON							
	5 Pulses / NAD 10	ON	OFF	OFF							
	10 Pulses / NAD 10	ON	OFF	ON							
	20 Pulses / NAD 10	ON	ON	OFF							
	100 Pulses / NAD 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept NAD 10						ON				
	Reject NAD 10						OFF				
★	Accept NAD 20 & 30							ON			
	Reject NAD 20 & 30							OFF			
★	Accept NAD 50 & 60								ON		
	Reject NAD 50 & 60								OFF		
★	Accept NAD 100									ON	
	Reject NAD 100									OFF	
★	Accept NAD 200										ON
	Reject NAD 200										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70+/L70F-NAD7(Pulse/ICT104U)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Credit - Pulse Normal High	ON			
Credit - Pulse Normal Low	OFF			
★ Pulse Mode		ON		
ICT104U Mode		OFF		
★ Reserved			ON	
			OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON		
★ ICT104U Mode		OFF		
★ Reserved			ON	
			OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	ICT104U
BV1	NAD 10	NAD 10
BV2	NAD 20	NAD 20
BV3	NAD 50	NAD 50
BV4	NAD 100	NAD 100
BV5	NAD 200	NAD 200
BV6	NAD 30	NAD 30
BV7	NAD 60	NAD 60